



TB-100

Termometri DN100.

Codice	Gambo (mm)	Scale Range	Attacco	Opzioni*	Imballo/conf	Min.ord.
PT509870	50	-30+50 °C	G1/2B	G	32/32	16
PT504470	50	0-60 °C	G1/2B	G	32/32	16
	50	0-80 °C	G1/2B	G	32/32	32
PT505070	50	0-120 °C	G1/2B	G+QISP	32/32	16
	50	0-140 °C	G1/2B	G+QISP	32/32	32
PT505870	50	0-200 °C	G1/2B	G	32/32	32
	50	0-250 °C	G1/2B	G	32/32	32
	50	0-350 °C	G1/2B	G	32/32	32
PT519870	100	-30+50 °C	G1/2B	G	32/32	16
PT514470	100	0-60 °C	G1/2B	G	32/32	16
	100	0-80 °C	G1/2B	G	32/32	32
PT515070	100	0-120 °C	G1/2B	G+QISP	32/32	16
	100	0-140 °C	G1/2B	G+QISP	32/32	32
PT515870	100	0-200 °C	G1/2B	G	32/32	32
	100	0-250 °C	G1/2B	G	32/32	32
PT516470	100	0-350 °C	G1/2B	G	32/32	32
PT51687000	100	0-500 °C	G1/2B	G	32/32	32
	150	-30+50 °C	G1/2B	G	32/32	32
PT52447000	150	0-60 °C	G1/2B	G	32/32	32
	150	0-80 °C	G1/2B	G	32/32	32
PT525070	150	0-120 °C	G1/2B	G+QISP	32/32	32
PT52587000	150	0-200 °C	G1/2B	G	32/32	32
PT52607000	150	0-250 °C	G1/2B	G	32/32	32
PT526470	150	0-350 °C	G1/2B	G	32/32	32
	150	0-500 °C	G1/2B	G	32/32	32
PT539870	200	-30+50 °C	G1/2B	G	32/32	32
	200	0-60 °C	G1/2B	G	32/32	32
	200	0-80 °C	G1/2B	G	32/32	32
PT535070	200	0-120 °C	G1/2B	G+QISP	32/32	32
	200	0-200 °C	G1/2B	G	32/32	32
	200	0-250 °C	G1/2B	G	32/32	32
PT536470	200	0-350 °C	G1/2B	G	32/32	32
	200	0-500 °C	G1/2B	G	32/32	32
	300	-30+50 °C	G1/2B	G	20/20	20
PT54447001	300	0-60 °C	G1/2B	G	20/20	20
	300	0-80 °C	G1/2B	G	20/20	20
PT54507001	300	0-120 °C	G1/2B	G+QISP	20/20	20
	300	0-200 °C	G1/2B	G	20/20	20
	300	0-250 °C	G1/2B	G	20/20	20
PT546470	300	0-350 °C	G1/2B	G	20/20	20
	300	0-500 °C	G1/2B	G	20/20	20

*Opzioni incluse

G = Completo di guaina in lega di rame

QISP = Quadrante conforme norme INAIL